

Mini Digital Clamp Tester

AC Current ,20A/200A ,23mm φ CT

Model 210



FEATURES

- 23mm φ CT window and ultra compact size.
- Data-hold function. Especially useful when working in dark or hard to get areas.

SPECIFICATIONS

Measuring method : Dual slope integration mode
 Display : 3.5 digit LCD, max. reading of 1999
 Range : AC 0~20A/200A

Accuracy 23°C ± 5°C 80%RH or less (50/60Hz)

Range	Resolution	Accuracy
AC 20A	10mA	± 1.2% rdg ± 5 dgt
AC 200A	100mA	± 1.2% rdg ± 5 dgt

Jaw opening capability : 23mm φ
 Over range indication : Blanking of all digits except MSD1
 Maximum indication : 1999
 Low battery indication : "B" mark on LCD
 Data hold indication : "DH" mark on LCD
 Sampling : 2 times/sec.
 Withstanding voltage : AC 2200V 1 minute max. (Between the core of CT and outer case)
 Operating temperature : 0°C to 40°C, 80%RH max. (Without condensation)
 Storage temperature : -10°C to 60°C, 70%RH max. (Without condensation)
 Power supply : 1.55V (SR-44, LR-44) × 2
 Power Consumption : 2.5mW
 Battery life : SR-44 (200 hours), LR-44 (100 hours)
 Size : 48(W) × 146(H) × 20(D)mm
 Weight : Approx. 80g
 Accessories : Soft case.....1
 Instruction manual.....1
 Batteries LR-44(1.55V).....2